



RECOMMENDED PCB LAYOUT

Meets MIL-C-39012, CECC 22110, IEC60169-15, Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-3GHz
Working Voltage	335V r.m.s	Withstanding Voltage	1000V r.m.s
Center Contact Resistance	≤3mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	Not Applicable
Durability	≥500 cycles	Temperature Range	-55°C to 155°C

3	Socket	1	Be. Copper	Gold
2	Insulator	1	Teflon	Natural
1	Body	1	Brass	Gold
No.	Description	QTY	Material	Finish

RoHS Compliant

© THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE NOTED TOLERANCES
SCALE 1:1
UNIT MM

APPROVED	JOHN
CHECKED	TERRY
DRAWN	Kevin
DRAWN DATE	July 07, 2012

APPROVED		JOHN		KEM KeMy Electronic Technology Inc.	
CHECKED		TERRY		TITLE	
DRAWN		Kevin		SMA (F) Jack, for PCB	
DRAWN DATE		July 07, 2012		DRAWING NO. KM-010129	
				REV 0	