



Part Number	Length (IN)	Length (MM)
KM-020242-0050	1.968±0.15	50±4
KM-020242-0100	3.937±0.15	100±4
KM-020242-0150	5.905±3%	150±3%
KM-020242-0200	7.874±3%	200±3%
KM-020242-0250	9.842±3%	250±3%

- Orient IPEX interface with respect to SMA 'D FLAT' as shown within ± 10°.
- Connector orientation is suggested for cable length less than 100mm.
- Additional lengths can be provided by changing XXXX to desired length in MM, or XXX in INCH, or XXM in METER.

4	Heat Shrink Tube	1	Black
3	IPEX MHF Plug	1	20278-112R-13
2	SMA (F) BHD Jack, Front Mount	1	KM-010131
1	Coaxial Cable	1	1.13mm
No.	Specification	QTY	Description

**RoHS Compliant**

\* MAJOR DIMENSION  
UNLESS OTHERWISE NOTED TOLERANCES

APPROVED  
**JOHN**

CHECKED  
**TERRY**

DRAWN  
**KEVIN**

THIRD ANGLE PROJECTION

SCALE 1:1 UNIT MM

DRAWN DATE  
Nov. 26, 2019

**KM** KeMy Electronic Technology Inc.

TITLE  
IP67/68 SMA (F) BHD Jack, Front Mount - 1.13mm - IPEX MHF Plug, Various Lengths

DRAWING NO. **KM-020242-XXXX**

REV  
A