

Waterproof led power supply CV-12060C

Features:

1. Protections: Short circuit/Overload/Over Voltage/Over Temperature
2. IP protection standard: IP67
3. 100% full load burn-in test
4. Certificate: CE, ROHS
5. Cooling: By Convection
6. MTBF: Min250Khrs
7. Efficiency: more than 80%

Specifications:

| | | |
|-------------------------------|---------------------------------------|--|
| Input Voltage | 170-250VAC | |
| Input current | 0.47A | |
| Input Frequency | 47 to 63 Hz | |
| Output Voltage | 12VDC | |
| The sum output current | 5A | |
| Max output Power | 60W | |
| Storage temperature: | -40-80 degree | |
| Operating temperature: | -25-45 degree | |
| Humidity operating: | 20%-95% | |
| Humidity storage: | 10%-95% | |
| Protections | Short Circuit | Auto recovery |
| | Over-load | 20% exceed is allowed |
| | Over-voltage | ≤255V |
| | Thermal Protection | ≤85 degree |
| CE | CE Safety Standard | Compliance to EN61347-1:2008&EN 61347-2-13:2006 |
| | EMI conduction & radiation | Compliance to EN 55015: 2006+A1: 2007 EN 61547: 2004 |
| | Harmonic Current | Compliance to EN 61000-3-2: 2006 EN 61000-3-3: 1995+A1: 2001+A2: 2005 |
| Others | Dimension/Weight | 175*67*50MM/850g |
| | Packing/Carton Size | 24pcs/carton / 39.4*25.4*24.5cm |
| | Cable | The wire of VDE, output with 2 groups 18#2C(300mm) |
| | Housing Material | Aluminum |