


3. Safety authentication 安全认证

SCHEMATIC DIAGRAM



1. Specifications 技术特性表

RATINGS 额定值	16 (4)A 250VAC 5E4 10T105
ELECTRONICAL LIFE 电气寿命	16 (4)A 125/250VAC 16A125VAC T105
TEMPERATURE 温度等级	16GPA 125/250VAC 10A 30VDC 1/3hp 125VAC 5E4 40T105 50-60Hz
INSULATION STRENGTH 绝缘电阻	100MΩ MIN
TEST VOLTAGE 耐电压	AC1000V/2000V
CONTACT RESISTANCE 接触电阻	50mΩ MAX
OPERATING FORCE 动作力 (OF)	1.1N MAX
RELEASE FORCE 释放力 (RF)	0.2N MIN
OPERATING POSITION 动作位置	21.4 ± 1.2mm
MOVEMENT DIFFERENTIAL 差动行程 (MD)	1mm MAX

2. Parts List OF TYPE KW3A 零件材质表

No.	Name 名称	Material 材料
1	BUTTON 开关子	Bakelite PF2A5-151J (b) 黑色 电木粉
2	LEVER 杠杆	Brass alloy H62, Silver plated 黄铜, 镀银
3	CASE 基座	Plastic PBT4308 (灰色) 工程塑料
4	PLATE MOVING 可动片	Brass alloy H62, Silver plated 黄铜, 镀银
5	TERMINAL 支架	Brass alloy H65, Silver plated 黄铜, 镀银
6	CONTACT 静触点	AgNi10/Cu 银-镍/铜
7	TERMINAL 端子	Brass alloy H65, Silver plated 黄铜, 镀银
8	TERMINAL 端子	Brass alloy H65, Silver plated 黄铜, 镀银
9	CONTACT 动触点	AgNi10/Cu 银-镍/铜
10	SPRING 簧片	Beryllium alloy QBe2 铍青铜
11	MOVING ARMS 动臂	Armor plate SPCC-SD, Nickel plated 钢板, 镀镍
12	COVER 盖	Plastic PBT4308 (灰色) 工程塑料

DESIGN	陈丹琼 20140408	KW3A-16Z5-D200
CHECKED BY	柴国旗 20140408	
TECHNICS		AVY8 3.604.016-775
EDITION	20140408	DONGNAN ELECTRONICS
PROJ		
STANDARDIZATION		
APPROVED BY	江小林 20140408	