



绕线方式如上图:
HANKING

⑤	TERMINAL: 6mm BOOTLACE FERRULES TERMINAL, BRASS 端子: 6mm包铜, 黄铜	2	pcs
④	PLUG PVC: KCS70-5001-85, BLACK 插头料: KCS70-5001-85, 黑色	40	g
③	HOSING: TWO-CORE SAA 10A 250V PLUG INNER SHELL, WHITE 塑壳: 10A 250V SAA两插塑壳, 白色	1	pcs
②	TERMINAL: TWO-CORE SAA 10A 250V PLUG L&N POLARITY, TERMINAL 端子: 10A 250V SAA半绝缘插片, 镀镍	2	pcs
①	CABLE: H05VV-F 2 × 0.75mm ² 24/0.20BS*2.3*2C (BROWN、BLUE)*6.2 BLACK L=5000mm 线材: H05VV-F 2 × 0.75mm ² 24/0.20BS*2.3*2C (棕、蓝)*6.2 黑色 L=5000mm	1	pcs
ITEM	DESCRIPTION	QTY	UNIT

				DRAWING NO: 图号		DRAWN BY P. E: HAN		DATE 19. 7. 31		NINGBO A-LINE CABLE AND WIRE CO., LTD CONNECT THE WORLD	
				AL030327-2794		CHECKED BY S. A:		DATE		CLIENT CODE: AL030327	
00	-	19. 7. 31	RTM	HAN			APPROVED BY MGR:		DATE		CUSTOMER PART NO: 货号
REV	ECO	DATE	REMARK	CHG' D BY	CHG' D BY	DIMENSIONS IN MM DWG NOT TO SCALE				VT912373	