H8.5×2

1/4-36UNS

5.3

5.4

15

Length

SQ4

15

H8

0.5

Part Number	Length (IN)	Length (MM)
KM-020832-002	2±0.12	50.8±3
KM-020832-0100	3.936±0.12	100±3
KM-020832-006	6±3%	152.4±3%
KM-020832-0200	7.873±3%	200±3%
KM-020832-010	10±3%	254±3%

Ø6.5

6

RECOMMENDED
PANEL CUTOUT

- Orient MMCX plug interface with respect to SMA 'D FLAT' as shown within ± 10°, for cable length less than 200mm only.
- Additional lengths can be provided by changing XXXX to desired length in MM, or XXX to desired length in INCH.
- Any queries feel free to consult our sales team at SALES@DGKEMY.COM

No.	Specification	QTY	Description
4	Adhesive Shrink Tube	2	Black
3	MMCX (M) R/A Plug	1	KM-011048-R1
2	SMA (F) Front Mount Jack	1	KM-011022-R1
1	Coaxial Cable	1	RG178

RoHS
Compliant

THIRD ANGLE PROJECTION

* MAJOR DIMENSION

UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
JOHN

CHECKED
TERRY

DRAWN
KEVIN

DRAWN DATE
Sep. 21, 2015

KM KeMy Electronic Technology Inc.

TITLE
SMA (F) Front Mount Jack Waterproof - RG178
- MMCX (M) R/A Plug, Various Lengths

DRAWING NO.
KM-020832-XXXX

REV
A