



Meets MIL-C-39012, IEC60169-15, CECC 22110, Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-6GHz
Working Voltage	<335V r.m.s	Withstanding Voltage	1000V r.m.s
Center Contact Resistance	≤3mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.25
Durability	≥500 cycles	Temperature Range	-65°C to 165°C

3	Socket	1	Beryllium Bronze	Gold
2	Insulator	1	PTFE	Natural
1	Body	1	Brass	Gold
No.	Description	QTY	Material	Finish
8			7	6

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
JOHN
CHECKED
TERRY
DRAWN
Kevin
DRAWN DATE
Mar. 05, 2008

KM KeMy Electronic Technology Inc.

TITLE
SMA (F) Jack to SMA (F) Jack Adapter

DRAWING NO. **KM-030145**

REV
0

All rights reserved. www.dgkemy.com